TRAILER AIR SUSPENSION SYSTEMS



The **TA25** family is a primary trailer suspension with a rated capacity of 25,000 pounds. The TA series delivers rugged performance, excellent ride quality and is ideal for numerous applications including, lowboy, drop-deck and container chassis.

- 25,000-pound suspension capacity
- Ride heights up to 19 in.
- Extended-life bushings
- ALIGN-TRAC™ Quick, easy alignment system
- 5-year limited warranty*
- * Contact your local W&C representative for complete warranty terms, conditions and limitations.



For more information, call 800.445.0736





Proven technology that delivers in the most rugged conditions. The TA25 suspension delivers value to the end user with its unmatched durability and is backed by W&C with world-class customer service.

TA25 Specifications







TOP MOUNT		LOW MOUNT	UNDER MOUNT			
Capacity:	25,000 pounds	25,000 pounds	25,000 pounds			
Travel:	8 inches	9 inches	8.5 inches			
Lift:	3 to 4 inches	5.11 to 5.31 inches	2 to 5 inches			
Ride Heights:	14 to 19 inches	14 to 19 inches	5.5 to 14 inches			
Weight:	333 pounds	372 pounds	365 pounds			

Weight includes suspension kit only - axles not included

TA - Trailer Air North America	Dry Van & Reefer	Drop Frame Van	Auto Hauler	Container Chassis	Chip Van & Logging*	Flat or Platform	Lowboy & Drop Deck	Dump (Rear & Side)*	Dump (Bottom)*	Tanker*	Grain Hopper	Livestock
TA25T20	P			P		P						
TA25U20		P	Р				Р					
TA25L20	0					0						

P - Preferred O - Optional

* Use of P spindle is preferred for heavy-duty and wheel outset applications. Note: Specific applications that are not typical must be reviewed on a case by case basis.

Value Added Options

- Front lift kits
- Tire inflation systems
- Under beam lifts
- Easy adjustable center lifts
- Air kits
- Designed to help the operator save money and increase tire life
- 5-year limited warranty*
- Industry standard parts
- Technical support
- * Contact your local W&C representative for warranty terms, conditions and limitations.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable specifications from W&C and the respective vehicle manufacturer.

Contact W&C for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Contact W&C at 972.547.6020 for additional information.



W&C

725 E. University Drive, McKinney, Texas 75069 972.547.6020 • 800.445.0736 • Fax 972.542.0097

www.wcsuspensions-intl.com

