

SL0890TT

Indicates target Ride Height for this tabulation

		2000	3000	4000	5000	6000	7000	8000	Output at Ground
Drawing number	Ride Height								
100401-1	13.00	11	19	27	35	43	52	60	
	14.00	12	20	29	38	47	56	65	
	15.00	13	23	33	43	53	62	72	
100401-2	14.00	11	19	27	35	43	52	60	
	15.00	12	20	29	38	47	56	65	
	16.00	13	23	33	43	53	62	72	
100401-3	15.00	11	19	27	35	43	52	60	
	16.00	12	20	29	38	47	56	65	
	17.00	13	23	33	43	53	62	72	
100401-4	16.00	11	19	27	35	43	52	60	
	17.00	12	20	29	38	47	56	65	
	18.00	13	23	33	43	53	62	72	
100401-5	17.00	11	19	27	35	43	52	60	
	18.00	12	20	29	38	47	56	65	
	19.00	13	23	33	43	53	62	72	

Some capacities shown may not be best suited for the suspension based on too much brake force for the applied load. Therefore, braking capacity may have to be downsized to accommodate.

Pressure requirements are approximations and will need to be calibrated on a weigh scale capable of handling the Output at Ground forces in the above chart.

Weight of the axle, hubs and drums based on 215/75R 17.5 tires, steel wheels, and Cast Hubs and Drums -----